
URBAN SERIES



The ideal solar lighting solution for integration in rural roads, garden areas, bike lanes, pedestrian walks, parks and playgrounds.







KENLOK INTELLIGENT CONTROL UNIT

- Light control algorithm for greater battery autonomy
- Factory custom lighting programming
- Energy resources optimization to maximize the durability of the system
- Voltage and temperature measurement system
- Automatic daylight saving time adjustment
- Total control of streetlight parameters

Iumek TELEMANAGEMENT SYSTEM

Online platform for the management and monitoring of the solar lamps.

- Customized system design
- 🧹 Private server
- Warning / alarm system for operational issues
- ✓ Different access levels
- ✓ Data Export to Excel
- 🗸 Remote diagnosis





FEATURES

L

UMINAIRE	
Туре	LED
Power	20 - 50 W
Rated voltage	12 - 24 V
Efficiency	> 120 lm/W
ССТ	3000 - 4000 - 5700 K

SOLAR PANEL

Туре	Monocrystalline / Polycrystalline
Power	From 60 Wp
Lifespan	More than 25 years

BATTERY

Туре	VRLA (GEL or AGM)
Capacity	100 - 210 Ah
Maximum depth of discharge	50%
Autonomy	2 - 5 days

COLUMN

Height	4 - 7 meters
Material	Hot dip galvanised steel
Corrosion resistance	> 15 years
Additional protection	Polyester powder coating
Optional treatment	Antigraffiti protection
Wind resistance	120 km/h



© 2018 - EKIONA Iluminación Solar S.L. - The company reserves the right to make any changes to the models. Values subject to changes based on the needs of each project.