
OLINTU SERIES





The most efficient smart solar solution with lithium battery. Compact design with smooth, minimalist lines.






Anti-vandalism design

0 emissions to the atmosphere

?) Personalized study of needs






KENLOK INTELLIGENT CONTROL UNIT

- Light control algorithm for greater battery autonomy
- Factory custom lighting programming
- Energy resources optimization to maximize the durability of the system
- Voltage and temperature measurement system
- Automatic daylight saving time adjustment
- Total control of streetlight parameters

"ilumek TELEMANAGEMENT SYSTEM

Online plataform for the management and monitoring of the solar lamps



- ✓ Private server
- √ Warning / alarm system for operational issues
- ✓ Different access levels
- ✓ Data Export to Excel
- ✓ Remote diagnosis



FEATURES



LUMINAIRE

Type	LED
Power	20 - 50 W
Rated voltage	12 -14 V
Efficiency	> 150 lm/W
CCT	3000 - 4000 - 5700 K

SOLAR PANEL

Туре	Monocrystalline / Polycrystalline
Power	60 - 200 Wp
Lifespan	More than 25 years

BATTERY

Type	Li-lon (LiFePO4)
Capacity	20 - 100 Ah
Maximum depth of discharge	80%
Autonomy	2 - 5 days

COLUMN

Height	4 - 7 m
Material	Hot dip galvanised steel
Corrosion resistance	> 15 years
Optional protection	Polyester powder coating
Optional treatment	Antigraffiti protection
Wind resistance	120 km/h

HIGH EFFICIENCY LEDS



HIGH RESISTANCE TO THE CORROSION



SMART SOLUTION



MAXIMUM RELIABILITY





Miramon Technology Park Paseo Mikeletegi, 56 20009 · Donostia - San Sebastián info@ekiona.com www.ekiona.com

